

Product data sheet

Specifications



modular pushbutton BP - grey - 1 NO

18032

! Discontinued on: 13 June 2018

! Discontinued

Main

Product or component type	Push-button
Device short name	BP
Standards	IEC 60947-5-1 IEC 60669-1

Complementary

Contacts type and composition	1 NO
[Ie] rated operational current	20 A
[Ue] rated operational voltage	250 V AC
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Comb busbar and distribution block compatibility	ProDis
9 mm pitches	2
Height	82 mm
Width	18 mm
Depth	71.5 mm
Colour	Grey
Electrical durability	AC-22: 30000 cycles AC 50/60 Hz
Connections - terminals	Staggered tunnel terminal2 cable(s) 2.5 mm ² flexible with cable end Staggered tunnel terminal2 cable(s) 2.5 mm ² flexible without cable end Staggered tunnel terminal2 cable(s) 2.5 mm ² rigid with cable end Staggered tunnel terminal2 cable(s) 2.5 mm ² rigid without cable end

Environment

Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9 cm
Package 1 Width	1.8 cm
Package 1 Length	7 cm
Package 1 Weight	0.039 kg

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)

18032 is replaced by:

1x



Acti9 IPB 1NO single push button grey
A9E18032