



ACTUATOR AZM 161-B1

Data

General data

Material of the actuator	Stainless steel
Gross weight	27 g

Mechanical data

Actuator	straight
----------	----------

Note

Note (General)	minimum actuating radius on hinged guards in line with the plane of the actuator 150 mm minimum actuating radius on rotating guard systems via the narrow edge of the actuator 180 mm The axis of the hinge must be 5 mm above and in a parallel plane to the top surface of the solenoid interlock.
----------------	--


Pictures

Product picture (catalogue individual photo)



ID: kazm1f42
| 7.3 MB | .tif | 195.4 x 130.2 mm - 1954 x 1302 px - 254 dpi
| 142.4 kB | .jpg | 352.778 x 235.303 mm - 1000 x 667 px - 72 dpi
| 13.1 kB | .png | 74.083 x 49.389 mm - 210 x 140 px - 72 dpi

Dimensional drawing miscellaneous



ID: 1azm1b20

| 124.6 kB | .jpg | 352.778 x 306.211 mm - 1000 x 868 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 29/05/2023, 08:25