



## ELDE.NWS24

### Data

#### Ordering data

Product type description	ELDE.NWS24
Article number (order number)	101166000
EAN (European Article Number)	4250116200702
eCl@ss number, version 12.0	27-37-12-09
eCl@ss number, version 11.0	27-37-12-09
eCl@ss number, version 9.0	27-37-12-09
ETIM number, version 7.0	EC000204
ETIM number, version 6.0	EC000204

#### Approvals - Standards

Certificates	cULus CCC
--------------	--------------

#### General data

Standards	EN IEC 60947-5-1 EN IEC 60947-1
Versions	LED modulet
Design	With integrated LED

Installation conditions (mechanical)	arbitrarily
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	3 g

### General data - Features

Integral system diagnostics, general	Yes
--------------------------------------	-----

### Mechanical data

Installation instructions	pluggable
Mounting flange position	3

### Mechanical data - Connection technique

Termination	Screw terminals
Terminal designations	EN 50005 EN 50013
Cable section, minimum	0.5 mm <sup>2</sup> , rigid 0.5 mm <sup>2</sup> , flexible
Cable section, maximum	2.5 mm <sup>2</sup> , rigid 1.5 mm <sup>2</sup> , flexible

### Mechanical data - Dimensions

Length	46 mm
Width	10 mm
Depth	60 mm

### Ambient conditions

Degree of protection of clips or terminals	IP20
Ambient temperature	-25 ... +80 °C

### Ambient conditions - Insulation values

Rated insulation voltage  $U_i$  440 V

## Electrical data

Rated operating voltage 24 VAC

Rated operating voltage 24 VDC

## Status indication

Colour of the LED White

Note (LED switching conditions display) Supply voltage UB: 24 VAC/DC

## Pictures

### Product picture (catalogue individual photo)



ID: keldlf01

| 534,7 kB | .jpg | 352.778 x 494.594 mm - 1000 x 1402 px - 72 dpi

| 41,8 kB | .png | 74.083 x 103.717 mm - 210 x 294 px - 72 dpi

## Diagram




ID: krdlek01

| 16,9 kB | .cdr |

| 33,5 kB | .jpg | 352.778 x 79.022 mm - 1000 x 224 px - 72 dpi

| 2,1 kB | .png | 74.083 x 16.581 mm - 210 x 47 px - 72 dpi

## Operating principle



ID: krf--a05

| 19,5 kB | .cdr |

| 189,7 kB | .jpg | 352.778 x 711.2 mm - 1000 x 2016 px - 72 dpi

| 3,7 kB | .png | 74.083 x 149.225 mm - 210 x 423 px - 72 dpi

Schmersal Nordiska AB, F O Petersons gata 28, S-421 31 Västra Frölunda

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 29/05/2023, 08:40