



## AZ 061 K 08106

- 1 Actuating planes
- without cable ducts
- Thermoplastic enclosure
- Contact pin in actuator bridge
- transparent cover
- Self-cleaning through the frictional movement of the contact bridges
- Protection class IP20
- double-break switch
- fixing screws M4 Pozidriv self-forming, undetachable, captive

## Data

### General data

Standards	ASME-A15.5 CAN/CSA-B44.1 EN 81-20 EN 81-50
Enclosure material	Glass-fibre reinforced ultramid, self-extinguishing
Material of the housing cover	Glass-fibre reinforced ultramid, self-extinguishing
Gross weight	24 g

### General data - Features

Suitable for elevators	Yes
Number of safety contacts	1

### Mechanical data

Actuating panels	1
Mechanical life, minimum	10,000,000 Operations
Actuating stroke	7 mm

Actuating force	1.6 N
Mounting	Round holes

### Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable entry	2 x single conductor version with connecting funnel
Tightening torque of electrical connection, maximum	1.2 Nm
Notes	M4 slotted-head combination screws, similar to DIN 7984, with self-opening clamp plates
Note (Cable entry)	Without cable ducts

### Mechanical data - Dimensions

Width	50 mm
Height	27 mm
Depth	16 mm

### Ambient conditions

Degree of protection	IP20
Ambient temperature	-30 ... +70 °C
Relative humidity, maximum	95 %
Note (Relative humidity)	non-condensing

### Ambient conditions - Insulation values

Rated insulation voltage $U_i$	500 V
--------------------------------	-------

### Electrical data

Thermal test current	4 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	2 A

Utilisation category DC-13	200 VDC
Utilisation category DC-13	2 A
Switching element	Opener (NC)
Switching principle	Self-cleaning pressure contact
Material of the contacts, electrical	Silver-plated Cu rivets

## Scope of delivery


Scope of delivery	Actuator must be ordered separately.
-------------------	--------------------------------------

## Pictures

### Product picture (catalogue individual photo)



ID: kaz61f01  
| 591,0 kB | .jpg | 283.986 x 330.553 mm - 805 x 937 px - 72 dpi  
| 64,8 kB | .png | 74.083 x 86.078 mm - 210 x 244 px - 72 dpi



Schmersal Nordiska AB, F O Petersons gata 28, S-421 31 Västra Frölunda

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 29/05/2023, 09:02