



## SRB301HC/R-24V

- 3 safety contacts, STOP 0
- 1 Signalling output
- Suitable for the signal processing of outputs with contact sensors

## Data

### Approvals - Standards

Certificates	TÜV cULus CCC TILVA
--------------	------------------------------

### General data

Standards	EN IEC 62061 EN ISO 13849-1 EN IEC 60947-5-1 EN IEC 60947-5-3 EN IEC 60947-5-5 EN IEC 61508 EN IEC 60204-1 EN IEC 60947-1
Climatic stress	EN 60068-2-78
Enclosure material	Glass-fibre reinforced thermoplastic, ventilated
Gross weight	290 g

### General data - Features

Stop-Category	0
Electronic Fuse	Yes

Wire breakage detection	Yes
Cross-circuit detection	Yes
Removable Terminals	Yes
Start input	Yes
Feedback circuit	Yes
Reset edge detection	Yes
Earth connection detection	Yes
Integral system diagnostics, status	Yes
Number of auxiliary contacts	1
Number of LEDs	4
Number of normally closed (NC)	2
Number of safety contacts	3

### Safety classification

Standards	EN IEC 60947-5-1 EN IEC 61508
-----------	----------------------------------

### Safety classification - Relay outputs

Performance Level, stop 0, up to	e
Category, Stop 0	4
Diagnostic Coverage (DC) Level, Stop 0	≥ 99 %
PFH value, Stop 0	$2.00 \times 10^{-8}$ /h
Safety Integrity Level (SIL), Stop 0, suitable for applications in	3
Mission time	20 Year(s)
Common Cause Failure (CCF), minimum	65

### Mechanical data

Mechanical life, minimum	10,000,000 Operations
Mounting	Snaps onto standard DIN rail to EN 60715

## Mechanical data - Connection technique

Termination	rigid or flexible Screw terminals M20 x 1.5
Terminal designations	IEC/EN 60947-1
Cable section, minimum	0.25 mm <sup>2</sup>
Cable section, maximum	2.5 mm <sup>2</sup>
Tightening torque of Clips	0.6 Nm

## Mechanical data - Dimensions

Width	45 mm
Height	100 mm
Depth	121 mm

## Ambient conditions

Degree of protection of the enclosure	IP40
Degree of protection of the mounting space	IP54
Degree of protection of clips or terminals	IP20
Ambient temperature	-25 ... +60 °C
Storage and transport temperature, minimum	-40 °C
Storage and transport temperature, maximum	+85 °C
Resistance to vibrations	10 ... 55 Hz, Amplitude 0.35 mm
Resistance to shock	30 g / 11 ms

## Ambient conditions - Insulation values

Rated impulse withstand voltage U <sub>imp</sub>	4 kV
Overvoltage category	III

Degree of pollution 2

## Electrical data

Frequency range	50 Hz 60 Hz
Operating voltage	24 VAC -15 % / +10 % 24 VDC -10 % / +20 %
Ripple voltage	10 %
Rated operating voltage	24 VAC
Rated operating voltage	24 VDC
Rated AC voltage for controls, 50 Hz, minimum	20.4 VAC
Rated control voltage at AC 50 Hz, maximum	26.4 VAC
Rated AC voltage for controls, 60 Hz, minimum	20.4 VAC
Rated control voltage at AC 60 Hz, maximum	26.4 VAC
Rated AC voltage for controls at DC minimum	20.4 VDC
Rated control voltage at DC, maximum	28.8 VDC
Electrical power consumption	1.4 W
Electrical power consumption	3.3 VA
Contact resistance, maximum	0.1 $\Omega$
Note (Contact resistance)	in new state
Drop-out delay in case of power failure, typically	80 ms
Drop-out delay in case of emergency, typically	20 ms
Pull-in delay at automatic start, maximum, typically	100 ms
Pull-in delay at RESET, typically	20 ms
Material of the contacts, electrical	AgSnO. self-cleaning, positive drive

## Electrical data - Safe relay outputs

Voltage, Utilisation category AC-15 230 VAC

Current, Utilisation category AC-15 6 A

Voltage, Utilisation category DC-13 24 VDC

Current, Utilisation category DC-13 6 A

Switching capacity, minimum 10 VDC

Switching capacity, minimum 10 mA

Switching capacity, maximum 250 VAC

Switching capacity, maximum 8 A

### Electrical data - Digital inputs

Conduction resistance, maximum 40  $\Omega$

### Electrical data - Digital Output

Voltage, Utilisation category DC-12 24 VDC

Current, Utilisation category DC-12 0.1 A

### Electrical data - Relay outputs (auxiliary contacts)

Switching capacity, maximum 24 VDC

Switching capacity, maximum 2 A

### Electrical data - Electromagnetic compatibility (EMC)

EMC rating EMC-Directive

### Status indication

Indicated operating states Position relay K2  
Position relay K1

## Other data

Note (applications)	Guard system Emergency-Stop button Pull-wire emergency stop switches Two-hand control panels Safety mats
---------------------	--

## Note


Note (General)	Inductive loads (e.g. contactors, relays, etc.) are to be suppressed by means of a suitable circuit.
----------------	--

## Wiring example

Note (Wiring diagram)	<p>The wiring diagram is shown with guard doors closed and in de-energised condition.</p> <p>Relay outputs: Suitable for 2 channel control, for increase in capacity or number of contacts by means of contactors or relays with positive-guided contacts.</p> <p>The control recognises cross-short, cable break and earth leakages in the monitoring circuit.</p> <p>2 channel control shown for a guard-door monitor with two contacts, of which at least one contact has positive break, with external reset button (R). (H2) = Feedback circuit</p>
-----------------------	--

## Pictures

### Product picture (catalogue individual photo)



ID: ksr3f16  
| 1.4 MB | .jpg | 342.547 x 625.122 mm - 971 x 1772 px - 72 dpi  
| 94.8 kB | .png | 74.083 x 135.114 mm - 210 x 383 px - 72 dpi


### Symbol (technical standard)

K	n-op/y	t-cycle
20 %	525.600	1,0 min
40 %	210.240	2,5 min
60 %	75.087	7,0 min
80 %	30.918	17,0 min
100 %	12.223	43,0 min

ID: kformm02

| 191.1 kB | .jpg | 352.778 x 246.592 mm - 1000 x 699 px - 72 dpi

## Wiring example



ID: ksr3117

| 47.0 kB | .cdr |

| 164.5 kB | .jpg | 352.778 x 391.231 mm - 1000 x 1109 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 29/05/2023, 09:26