



IFL 15-30L-10TP

- Metal enclosure
- DC 3-wire
- Long design
- Design M30

Data

Ordering data

Product type description	IFL 15-30L-10TP
Article number (order number)	101127041
EAN (European Article Number)	4030661050829
eCl@ss number, version 12.0	27-27-40-01
eCl@ss number, version 11.0	27-27-01-01
eCl@ss number, version 9.0	27-27-01-01
ETIM number, version 7.0	EC002714
ETIM number, version 6.0	EC002714

Approvals - Standards

Certificates	CCC
--------------	-----

General data

Standards	DIN VDE 0660-208 EN IEC 60947-5-2
Housing construction form	Cylinder, thread
Installation conditions (mechanical)	not flush

Housing material	Brass
Housing coating material	nickel-plated
Active area	Plastic
Material of the nuts	Brass
Gross weight	195 g

General data - Features

Integral system diagnostics, status	Yes
Cable sleeve	Yes
Number of cable wires	3

Mechanical data

Tightening torque of nuts, maximum	30 Nm
------------------------------------	-------

Mechanical data - Switching distances according EN IEC 60947-5-3

Nominal switching distance S_n	15 mm
----------------------------------	-------

Mechanical data - Connection technique

Length of cable	2 m
Termination	Cable
Wire cross-section	0.34 mm ²
Material of the Cable mantle	PVC

Mechanical data - Dimensions

ISO thread of the sensor	M30
width across flats	36 BK
Length of sensor	100 mm

Ambient conditions

Degree of protection	IP67
Ambient temperature	-25 ... +70 °C
Protection class	0

Electrical data

No-load supply current I_0 , typical	3.5 mA
Rated operating voltage	10 ... 30 VDC
Operating current	200 mA
Switching element	Normally open contact (NO)
Protection circuit integrated	inductive interference protection Protection against polarity reversal Surge protection Max. fuse rating
Switching frequency, approx.	100 Hz
Type of voltage range	DC

Electrical data - Digital Output

Voltage drop U_d , maximum	1.2 V
Current at Voltage drop U_d	0.2 A
Design of control elements	p-type

Status indication

Note (Integral System Diagnostics, status)	yellow LED
---	------------

Note

Note (General)	Instead of nuts, a mounting clamp can be provided.
----------------	--

Ordering code

Product type description:
IFL (1)-(2)(3)-(4)(5)(6)(7)-(8)

(1)		
10		Switching distance 10 mm
15		Switching distance 15 mm
(2)		
30		Cylinder, thread M30, metal
300		Cylinder, thread M30, plastic
(3)		
without		Standard body
M		Miniature body
L		Long design
(4)		
01		Opener (NC)
10		Normally open contact (NO)
10/01		NO contact / NC contact with wiring compartment
11		1 NO contact / 1 NC contact antivalent
(5)		
without		Cable
ST		Male connector
T		Conductor with strain relief
D		DC 2-wire
(6)		
without		Standard connector version
2		Alternative connector version
(7)		
N		n-type
P		p-type
(8)		

1310

Can be used up to +110 C (for alternating current (AC) only)

2130

Can be used up to +130 C, without LED switching conditions display

1766

Can be used up to +110 C (for p-type or n-type only)

Pictures

Product picture (catalogue individual photo)




ID: kifl1f38

| 464.5 kB | .jpg | 352.778 x 529.167 mm - 1000 x 1500 px - 72 dpi

| 43.4 kB | .png | 74.083 x 111.125 mm - 210 x 315 px - 72 dpi

| 30.1 kB | .jpg | 82.197 x 123.472 mm - 233 x 350 px - 72 dpi

Dimensional drawing basic component




ID: lifl1g36

| 26.1 kB | .cdr |

| 6.8 kB | .png | 74.083 x 51.153 mm - 210 x 145 px - 72 dpi

| 93.9 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691 px - 72 dpi

Diagram



ID: id3lk05

| 31.7 kB | .cdr |

| 48.6 kB | .jpg | 352.778 x 146.756 mm - 1000 x 416 px - 72 dpi

| 2.3 kB | .png | 74.083 x 30.692 mm - 210 x 87 px - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, 42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 26/10/2023, 06:50