

Control and signaling units

Harmony XB5 plastic

Body/contact assemblies

Screw clamp terminal connections



ZB5AZ009



ZBE101



ZBE203



ZB5AZ101



ZBE201




ZB5AZ107



ZBE501



ZB2BE101



ZBZ001

Body/fixing collar

For use with	Sold in lots of	Unit reference	Weight kg/lb
Electrical block (contact or light)	10	ZB5AZ009	0.006/0.013

Contact functions ⁽¹⁾

Screw clamp terminal connections (Schneider Electric anti-loosening system)

Application	Type of contact	Description	NO	NC	NC MC (7)	Sold in lots of	Unit reference	Weight kg/lb
-------------	-----------------	-------------	----	----	-----------	-----------------	----------------	--------------

Contacts for standard applications

Contact blocks	Single		1	–	–	5	ZBE101	0.011/0.024
			–	1	–	5	ZBE102 (6)	0.011/0.024
	Double		–	–	1	5	ZBE302	0.014/0.030
			2	–	–	5	ZBE203	0.020/0.044
			–	2	–	5	ZBE204	0.020/0.044
	Single with body/fixing collar		1	1	–	5	ZBE205	0.020/0.044
			1	–	–	1	ZB5AZ101	0.021/0.046
			–	1	–	1	ZB5AZ102	0.021/0.046
			2	–	–	1	ZB5AZ103	0.030/0.066
			–	2	–	1	ZB5AZ104	0.030/0.066
		1	1	–	1	ZB5AZ105	0.030/0.066	
		1	2	–	1	ZB5AZ141	0.040/0.088	

Contacts for specific applications

Low-power switching	Single	Standard	1	–	–	5	ZBE1016	0.012/0.026	
			–	1	–	5	ZBE1026	0.012/0.026	
		Dusty environment (2) (IP5X, 50 µm dust)	1	–	–	5	ZBE1016P	0.012/0.026	
			–	1	–	5	ZBE1026P	0.012/0.026	
Staggered contacts	Single	Early make NO	1	–	–	5	ZBE201	0.011/0.024	
			–	1	–	5	ZBE202	0.011/0.024	
		Single with body/fixing collar	Overlapping NO+NC	1	1	–	5	ZB5AZ106	0.062/0.137
			Staggered NO+NO	2	–	–	5	ZB5AZ107	0.062/0.137
High-power switching	Single	Standard (3)	1	–	–	1	ZBE501	0.020/0.044	
			–	1	–	1	ZBE502	0.020/0.044	
			2	–	–	1	ZBE503	0.032/0.071	
			–	2	–	1	ZBE504	0.032/0.071	
			1	1	–	1	ZBE505	0.032/0.071	
Additional contact blocks for high-power switching	Single	Standard (4)	1	–	–	1	ZB2BE101	0.020/0.044	
			–	1	–	1	ZB2BE102	0.020/0.044	

Clip-on legend holder, sheet of blank legends

Description	Sold in lots of	Unit reference	Weight kg/lb
Clip-on legend-holder for electrical blocks with screw clamp terminal connections (5). For identification of an XB4B control or signaling unit	10	ZBZ001	0.001/0.002
Sheet of 50 blank legends for legend holder ZBZ001	10	ZBY001	0.023/0.051

(1) The contact blocks enable variable composition of body/contact assemblies. Maximum number of rows possible: 3. Either 3 rows of 3 single contacts or 1 row of 3 double contacts + 1 row of 3 single contacts (double contacts occupy the first 2 rows). Maximum number of contacts is specified on page 26 of this catalog.

(2) It is not possible to fit an additional contact block on the back of these contact blocks.

(3) It is not possible to fit an additional contact block on the back of these contact blocks or to use these contacts with light blocks.

(4) To be fitted on the back of ZBE50● contacts.

(5) This legend holder is not compatible with high-power switching contacts.

(6) To order products with screw clamp terminal connections for lugs, add a 9 at the end of the commercial reference. Example: ZBE102 becomes ZBE1029.

(7) NC contact block with monitoring dedicated for Emergency stop head only.